



KM-F650+

Plain Paper Laser Fax

BUSINESS SAVVY.
FAX FRIENDLY.



- ▶ Powerful Fax and Multifunctional Features in a Compact System
- ▶ 3 Second Per Page Fax Transmission Using Super G3 Modem
- ▶ Up to 760 Page Memory
- ▶ Fast 6.5 Pages Per Minute Print Speed
- ▶ Large 250 Sheet Standard Capacity Expandable to 500
- ▶ TWAIN Compatible 400 dpi Scanning
- ▶ High Quality 600 dpi Printing

KM-F650+ SPECIFICATIONS

BASIC SPECIFICATIONS:

Configuration:	Desktop Facsimile with 33.6Kbps Modem and 250 Sheet Cassette,
Compatibility:	ITU-T Group 3
Scanning Resolution:	Standard: 203 dpi x 98 lpi Fine: 203 dpi x 196 lpi Super Fine: 203 dpi x 391 lpi Ultra Fine: 406 dpi x 391 lpi (interpolated)
Print Resolution:	Fax / Copy: 406 dpi x 391 lpi Print: 600 dpi x 600 dpi
Fax Memory:	8MB
Memory Capacity:	480 pages
Document Memory Backup:	Flash Memory
Coding System:	MH/MR/MMR
Scanning Method:	CCD
Print Method:	Monochrome Laser
Max Print Width:	8.2"
Electrical Requirements:	108 – 132V, 47 – 63Hz
Dimensions:	14.6"W x 18.5"D x 9.9"H
Weight:	19.8 lbs

SPEEDS:

Modem Speed:	33.6Kbps with Auto Fallback
Transmission Speed:	Approx. 3 Seconds per Page
Pages Per Minute:	6.5 Letter Copy & Print

PAPER SUPPLY:

Standard Paper Source:	250 Sheet Drawer
Drawer Paper Size:	8.5" x 11", 8.5" x 14"
Std / Max Paper Capacity:	250 / 500
Paper Weight:	16 – 20 lb Bond

DOCUMENT PROCESSOR:

Type:	Automatic Document Feeder (ADF)
Acceptable Originals:	5.8" x 5" – 10.1" x 78.77"
Capacity:	50 Sheet
Paper Weight:	12 – 24 lb Bond
Effective Scanning Width:	8.3"
Quick Scan Speed:	Standard: 2.8 Seconds

FAX FUNCTION:

DIALING CAPABILITIES:

One-Touch Dialing Keys:	28
Program / One-Touch Keys:	4
Speed, Dialing Codes:	100
Total Numbers Stored:	132
Redial Attempts / Intervals:	Up to 5 / 1 to 15 minutes
Group Dialing:	4 Groups / 131 numbers
Other Dialing:	Chain Dialing, Directory Search Dialing, Pulse / Tone Dialing
Max Dialing Digits:	36

ADDITIONAL FAX FEATURES:

Transmission / Reception:	Multi Access, Memory Transmission, Quick Memory Transmission, Delayed Transmission (10 timers), ECM, Auto Fax/Tel. Switch, Polling (144 locations), Memory Polling, Continuous Polling, Verification Stamp, Broadcast Transmission (144 locations), Distinctive Ring Detection (DRD), Memory Reception, Delayed Polling, Delayed Multi-Station Polling (10 timers / 144 locations), Substitute Reception, Auto Reduction
Security Communication / Codes:	Confidential Transmission / Reception (10 mailboxes), Password Communication, Access Codes
Journals and Lists:	Transaction Journal, Communication Journal, One Touch List, Abbreviated Number List, Program List

UTILITIES:

Configuration Editor, Phonebook Editor
--

PRINT:

Std Memory:	5MB DRAM
Windows® OS Compatibility:	Windows® 98/Me/NT4.x/2000/XP
Connectivity:	Standard Parallel IEEE1284
Driver:	GDI Driver for Windows®
Utilities:	Status Monitor

SCAN:

Resolution:	400 x 400 dpi
File Format:	PDF,TIFF, JPEG, Bitmap
Connectivity:	Standard Parallel IEEE1284
Scanning Type:	PC Scanning
Driver:	TWAIN
Utilities:	Standard Document Management Software

COPY FUNCTION:

Continuous Copy:	Up to 99
Reduction/Enlargement:	70% – 100%

PAPER HANDLING OPTIONS:

PAPER DRAWER: PF-40

Paper Capacity:	250 Sheets
Paper Weight:	16 – 20 lb Bond
Paper Size:	8.5" x 11", 8.5" x 14"
Dimensions / Weight:	13.7"W x 16.9"D x 3.2"H / 5.5 lbs

ADDITIONAL OPTIONS:

Telephone Handset (HS-40)

CONSUMABLES:

TK-40	All-In-One Cartridge 9,000 pages@ 3% Coverage*
*based on ITU-T No. 1 chart in standard mode	
Ships with one TK-40 All-In-One Cartridge	



Specifications and design are subject to change without notice.
For the latest on connectivity visit www.kyoceramita.com.
All trademarks are the property of their respective owners.

Kyocera Mita America, Inc. Headquarters: 225 Sand Road, PO Box 40008,

Fairfield, NJ 07004-0008, USA
©2007 Kyocera Mita America, Inc.
IC# 855D400052



www.kyoceramita.com